

# **EXTRA WHITE GLUE**

## **TECHNICAL DATA SHEET**

#### CHARACTERISTICS AND APPLICATIONS

FOR BONDING THAT REQUIRES GREATER STRENGTH. PVA adhesive with high bonding strength and flexibility, ideal for wooden artifacts, laminates, paper, cardboard, among others. Especially recommended for furniture assembly. Water-based product, non-toxic, with a mild odor and easy to apply. It is indicated for high performance bonding in medium and low density woods, agglomerates, laminates, paper, cardboard and porous surfaces in general. It can be used in cold and hot bonding processes.

### INSTRUCTIONS FOR USE AND HANDLING

**HOW TO USE:** The surfaces to be glued must be clean, flat and dry. Apply the adhesive evenly. Join the parts immediately, keeping them under pressure, for two to three minutes, in order to increase the efficiency of the bonding.

#### **BENEFITS**

- ·Ready to use
- Water-based, solvent-free technology
- Non-toxic product
- Easy handling and cleaning
- Mild odor
- High bond strength
- •Excellent flexibility, ideal for bonding materials that suffer mechanical
- Optimal viscosity

## **PROPERTY**

UNIT TEST RESULT	UNIT TEST RESULT	UNIT TEST RESULT
Product Appearance	Visual	White Liquid
Film Appearance	Visual	Translucent Flexible
Viscosity	cР	5.500 a 8.500
ph (25°C)	-	4 a 6
Density	g/cm³	1,03 a 1,12
Solid content	%	15,5 a 18,5

#### **STORAGE**

The product must be kept in its original packaging and stored in a cool place at a temperature of 5 to 30°C, protected from direct sunlight and away from heat sources. To avoid contamination of the unused product, do not return any leftover material in its original packaging. Keep the container closed to prevent skin formation. Validity (from the date of manufacture): 13 months.

#### LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).







unipega.com





