

TECHNICAL DATA SHEET

CHARACTERISTICS AND APPLICATIONS

One-component adhesive based on hybrid polymer with modified silanes. Possui high initial tack (immediate grip) for extra strong collagens up to 350kg, in various materials* (except PE, PP and PTFE), from metal, concrete, aluminum, stone, marble, ceramic, tile, glass, polycarbonate, PVC, wood, PVC and others. It can be applied in any climatic condition and even on wet surfaces. With UV resistance and no solvents, Unipega High Tack Ultra can be used for interiors and exteriors, oil paint and does not stain or substrate.

INSTRUCTIONS FOR USE AND HANDLING

SURFACE PREPARATION: The surface must be dry, clean, free of dust and oils. Remove all material residues, especially those that are not sufficiently adhered to the layers (sand if necessary). Clean and degrease the surface with isopropyl alcohol and keep it dry before application. Do not use kerosene or gasoline to clean the surfaces. For a better finish, it is recommended to use adhesive tape on the side areas of the joint where the product is not intended to come into contact. In the case of applications on substrates other than those mentioned, it is recommended to carry out a test to assess the adhesion and compatibility of the product.

HOW TO USE: GENERAL GLUING: Apply the product to the desired area and immediately finish. To glue very heavy pieces, use a shim. If using adhesive tape, remove it before it forms a film. **FIXING MIRROR:** Check the condition of the substrate (wall, tile, wood, etc.), which must be clean and level. Apply double-sided tape to the mirror. Apply the product in vertical lines 10 mm wide and 6 mm high as shown in the figure. Join the surfaces, keeping a minimum distance of 3 mm between the mirror and the substrate and do not exceed 5 minutes. Check the positioning of the mirror before joining it to the substrate, as the tape does not allow repositioning. Use support shims when installing the mirror to aid the initial process of fixing the mirror. Remove the shims at least 6 hours after installation. Note: Installation must follow the recommendations according to ABNT NBR 15198 – SILVER MIRROR – PROCESSING AND INSTALLATION. **FIXING THE BOWL:** Apply the product to the bowl and immediately press it against the stone. Wait 6 hours before moving the bowl and 24 hours before using it. After use, leave a small amount of product above the spout to form a plug. When reusing, remove the plug. After opening, reuse the product within one week. Clean the tools before curing. After curing, the product can only be removed mechanically.

PROPERTY

UNIT TEST RESULT	UNIT TEST RESULT	UNIT TEST RESULT
Skin time	min	20
Curing time	mm/24h	4,0
Density	g/cm³	1,40
Hardness	Shore A	50
Tensile strength	MPa	3,0
Elongation	%	150
Temperature application	°C	5 a 40
Temperature resistance	°C	-40 / +90

COLORS

COLOR	REFERENCE RAL
WHITE	9003

Mirror Area (m2)	Mirror Thickness (mm) x Cord Length (cm)		
	4mm	5mm	6mm
0,50	10cm	13cm	15cm
0,75	15cm	19cm	23cm
1,00	20cm	25cm	30cm
1,25	25cm	32cm	38cm
1,50	30cm	38cm	45cm
1,75	35cm	44cm	53cm
2,00	40cm	50cm	60cm
2,50	50cm	63cm	75cm
3,00	60cm	75cm	90cm



Illustrative image of cords application

LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. **For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).**



unipega.com

info@unipega.com

f /unipegaoficial

@unipega_oficial

Unipega

Unipega

TECHNICAL DATA SHEET

LIMITATIONS

Do not apply to aquariums. Do not apply to plastics based on polyethylene, polypropylene, nylon®, acrylic and polytetrafluoroethylene. Do not apply to parts that will come into contact with food or be continuously immersed in liquid media. Do not apply to glass facades or any structural adhesion that requires resistance. Do not apply to movement joints and building facades. Before painting, it is recommended to perform a pre-test. Solvent and oil-based paints can be harmful to the product.

STORAGE

The product must be kept in its original packaging and stored in a cool place at a temperature of 5 to 30°C, away from direct sunlight and heat sources. To avoid contamination of unused product, do not return any leftover material in its original packaging. Keep out of reach of children and pets. Shelf life (from date of manufacture): 12 months.

LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. **For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).**



unipega.com

info@unipega.com



/unipegaoficial



@unipega_oficial



Unipega



Unipega