

TECHNICAL DATA SHEET

CHARACTERISTICS AND APPLICATIONS

One-component, acetic-curing silicone sealant suitable for sealing and bonding aluminum, glass, tiles, sanitary ware and shower enclosures. Resistant to the formation of fungi. With non-sagging properties, it cures with atmospheric humidity, transforming into a flexible and resistant rubber.

INSTRUCTIONS FOR USE AND HANDLING

SURFACE PREPARATION: The surface must be dry, clean, free of dust and oils. Remove all material residues, especially those that are not sufficiently adhered to the layers (sand if necessary). Clean and degrease the surface with isopropyl alcohol and keep it dry before application. Do not use kerosene or gasoline to clean the surfaces. For a better finish, it is recommended to use adhesive tape on the side areas of the joint where the product is not intended to come into contact. In the case of applications on substrates other than those mentioned, it is recommended to carry out a test to assess the adhesion and compatibility of the product.

HOW TO USE: Apply the product to the desired area and immediately finish. If using adhesive tape, remove it before it forms a film. After use, leave a small amount of product above the nozzle to form a plug. When reusing, remove the plug. After opening, reuse the product within one week. Clean the tools before curing. Once cured, the product can only be removed mechanically.

PROPERTY

UNIT TEST RESULT	UNIT TEST RESULT	UNIT TEST RESULT
Skin time	min	10
Curing time	mm/24h	3,0
Density	g/cm ³	0,94
Hardness	Shore A	14
Tensile strength	MPa	1,3
Elongation	%	500
Temperature application	°C	5 a 35
Temperature resistance	°C	-40 / +120

COLORS

COLORS	REFERENCE RAL
COLORLESS	-
WHITE	9003
GRAY	7037
BLACK	9017

LIMITATIONS

Do not apply to laminated glass, corrosive metals, mirrors, painted surfaces, aquariums and concrete. Do not apply to plastics based on polyethylene, polypropylene, polycarbonate, acrylic and polytetrafluoroethylene. Do not apply to parts that will come into contact with food or be continuously immersed in liquid media. Do not apply to glass facades or any structural adhesion that requires resistance. Does not accept paint.

STORAGE

The product must be kept in its original packaging and stored in a cool place at a temperature of 5 to 30°C, away from direct sunlight and heat sources. To avoid contamination of unused product, do not return any leftover material in its original packaging. Keep out of reach of children and pets. Shelf life (from date of manufacture): 12 months.

LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. **For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).**



unipega.com

info@unipega.com

f /unipegaoficial

@unipega_oficial

Unipega

Unipega