

TECHNICAL DATA SHEET

CHARACTERISTICS AND APPLICATIONS

Unipega Skirting Board Glue is a solvent-free acrylic resin-based glue for fixing skirting boards, skirting boards, ceiling skirting boards and rosettes. It adheres to plastic*, wood, tile, brick, plaster, cardboard and MDF. It has high adhesion to ensure perfect adhesion. Easy to apply and remove excess, without sticking to the skin. It can be painted and sanded after complete curing. Resistant to humidity and mold formation.

INSTRUCTIONS FOR USE AND HANDLING

SURFACE PREPARATION: The surface must be dry, clean, free of dust and oils. Remove all material residues, especially those that are not sufficiently adhered to the layers (sand if necessary). Clean and degrease the surface with isopropyl alcohol and keep it dry before application. Do not use kerosene or gasoline to clean the surfaces. For a better finish, it is recommended to use adhesive tape on the side areas of the joint where the product is not intended to come into contact. In the case of applications on substrates other than those mentioned, it is recommended to carry out a test to assess the adhesion and compatibility of the product.

HOW TO USE: Apply the glue to the surface of the piece to be glued and to its seams. Press the piece against the wall and/or ceiling and remove excess glue with a spatula, cleaning the edges with a damp sponge. To improve the finish of the joints, wet sandpaper can be used on the joints between the pieces.

PROPERTY

UNIT TEST RESULT	UNIT TEST RESULT	UNIT TEST RESULT
VOC Index (Volatile Organic Compounds)	g/L	5
Appearance	Visual	Pasty
Open time	min	11
Total cure time (at 20°C)	h	48h (porous materials) and 72h (non-porous materials)
Application temperature	°C	10 to 40
Temperature resistance (after final cure)	°C	-20 / +80

COLORS

COLOR	REFERENCE RAL
WHITE	9003

LIMITATIONS

Do not apply to mirrors and aquariums. Do not apply to plastics based on polyethylene, polypropylene, nylon®, acrylic and polytetrafluoroethylene. Do not apply to materials that will come into contact with food and will be continuously immersed in liquid media. Do not apply to structural adhesion that requires resistance. Do not apply to surfaces that eliminate oil, plasticizers or solvents, such as wood immersed in oil, wet surfaces, walls with coating in the process of peeling. For gluing, it is necessary that at least one of the substrates is porous. Before painting, it is recommended to perform a pre-test. Solvent and oil-based paints can be harmful to the product.

STORAGE

The product must be kept in its original packaging and stored in a cool place at a temperature of 5 to 30°C, away from direct sunlight and heat sources. To avoid contamination of unused product, do not return any leftover material in its original packaging. Keep out of reach of children and pets. Shelf life (from date of manufacture): 18 months.

LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. **For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).**



unipega.com

info@unipega.com

f /unipegaoficial

@unipega_oficial

Unipega

Unipega