

STRONG FIX FIXING TAPE

ULTRA STRONG FIXING TAPE FOR INDOOR AREAS

FEATURES AND APPLICATIONS

Strong Fix Tape Unipega is ideal for ultra strong fixations, replacing the use of nails and screws. It can be used to fix frames, key holders, mirrors, decorative objects, electrical conduits and many others. It's easy, safe and clean to use, avoiding the need of drilling surfaces. It can be applied to any smooth surface, such as walls, acrylics, glass, plastics, metals, wood (varnished or painted) and tiles, indoors use. It does not yellow over time.

BENEFITS

- Extreme and permanent fixation
- Replaces the use of nails and screws
- Fast, easy, safe and clean application
- Ideal for indoor areas
- Does not yellow



Portrait




Keychain



Mirror



Decoration Object



Hook



Paper Support

PRESENTATION	COLOR	SALES CODE	BAR CODE	PACKING		NCM	BOX							PALLETIZING
				Weight (g)	Measure (LxA) mm		Code	Unit	Net Weight (kg)	Gross Weight (kg)	Length (mm)	Width (mm)	Height (mm)	
9mm x 2m	Transparent	0535.0003	7898652121265	26	90x160	35061090	17898652121262	12	0,312	0,412	230	200	100	Base: 24 Height: 11
12mm x 2m		0535.0004	7898652121272	33			17898652121279		0,396	0,496				
19mm x 2m		0535.0005	7898652121289	48			17898652121286		0,576	0,676				
24mm x 2m		0535.0006	7898652121296	60			17898652121293		0,720	0,820				

INSTRUCTIONS FOR USE AND HANDLING

HOW TO USE
Before fixing the tape, pre-mark the desired area with a pencil. Make sure that the surface and the object to be fixed are free of dirt and oil. To ensure fixation, the surface must be smooth and without irregularities. Cut the tape to the size and quantity sufficient to support the object (check the recommendation specified on the card). Apply the tape to the object and remove the protective film. Press the object against the surface to be fixed for 1 minute. Important: The tape will only have 100% of its load capacity after 48 hours. Ideal application temperature range: 5°C to 40°C.

LIMITATIONS

Do not apply in places with the presence of solvents. Application on wallpapers or other delicate or freshly painted surfaces is not recommended. Do not use in structural applications. Do not overlap pieces of tape.

STORAGE

The product must be kept at a temperature of 25°C and 50% relative humidity, away from direct sunlight and away from heat sources. Do not expose to the sun and temperatures above 50°C.
Validity (from the date of manufacture): 24 months.

LIMITED WARRANTY INFORMATION

The information contained in this Safety Data Sheet is based on our knowledge and experience to date. Because our product can be used in a wide range of applications and under different working conditions, we recommend that the customer carry out their own tests to approve the product for safety and purpose of use. We cannot take responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the user's full responsibility to determine the suitability of the product for the desired purpose and to adopt the precautions that may be advised to protect goods and people against any dangers that may be involved in its handling and application. Our guarantee applies in the context of the legal rules and the provisions in force, the professional rules in force and in accordance with the provisions established in our general conditions of sale. The information detailed in this document is given as an indication. The same applies to any information provided verbally, over the phone or in writing to any potential or existing customer. For safety, handling, storage and disposal information, consult the respective Safety Data Sheet (SDS).



unipega.com

info@unipega.com

f /unipegaoficial

@unipega_oficial

Unipega

Unipega