

TECHNICAL DATA SHEET

CHARACTERISTICS AND APPLICATIONS

REDUCES FRICTION AND WEAR. Unilub is a general purpose lubricant developed to reduce friction and, consequently, wear between metal parts, eliminating noise and lubricating completely due to its high penetrating power. It protects for much longer against rust and weather. In the industry, it lubricates and protects machines, light and heavy tools, bearings, conveyors, safety valves, shafts, electric motors, gears, pulleys and other industrial equipment, automotive mechanical parts, from cables, pedals, gears, pulleys and even electrical parts. In general use, it can be used in locks, hinges, latches, tools, appliances, sewing, washing and other machines, bicycles and any metal part.

INSTRUCTIONS FOR USE AND HANDLING

SURFACE PREPARATION: The surface must be dry, clean, free of dust and oils. Remove all material residues, especially those that are not sufficiently adhered to the layers (sand if necessary). Clean and degrease the surface with isopropyl alcohol and keep it dry before application. Do not use kerosene or gasoline to clean the surfaces. For a better finish, it is recommended to use adhesive tape on the side areas of the joint where the product is not intended to come into contact. In the case of applications on substrates other than those mentioned, it is recommended to carry out a test to assess the adhesion and compatibility of the product.

HOW TO USE: It must be applied to the surface to be lubricated or ungripped with the aid of the extender thus increasing its penetrating power. After application wait a few minutes for better penetration of the product in the parts to be ungripped. It can be used in the normal position or upside down.

BENEFITS

- Easy application
- Reduces friction
- Eliminates noise
- Protects against rust and weather
- Multipurpose
- Because it does not have CFC, it does not cause damage to the ozone layer

LIMITATIONS

It should not be used in food or in containers that may come into contact with food.

STORAGE

The product must be kept in its original packaging and stored in a cool place at a temperature of 5 to 30°C, protected from direct sunlight and away from heat sources, with the packaging always facing upwards. Do not expose to the sun and temperatures above 50°C. Avoid keeping the product inside vehicles. Keep out of reach of children and pets. Validity (from the date of manufacture): 36 months.

LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).



unipega.com

info@unipega.com



/unipegaoficial



@unipega_oficial



Unipega



Unipega