

## TECHNICAL DATA SHEET

### CHARACTERISTICS AND APPLICATIONS

PROTECTS UPHOLSTERY, CUSHIONS, CURTAINS, CAR SEATS, SNEAKERS, BAGS, LUGGAGE, CLOTHING IN GENERAL AND MUCH MORE. Unipega Fabric Protector is indicated to protect fabrics from undesirable stains caused by liquids and other substances, providing the fibers with greater resistance and maintaining the original color and texture for much longer. Can be applied to fabrics, benches and sofas.

### INSTRUCTIONS FOR USE AND HANDLING

**HOW TO USE:** On a clean, dry fabric, shake the packaging vigorously and apply the Unipega Tissue Protector to the location to be protected at a distance of approximately 15 centimeters in uniform motion to moisten the fabric, but without soaking it. Wait 5 minutes and apply a new coat in the opposite direction to the previous one. Repeat the process three times. The minimum drying time to touch is 3 to 4 hours and the total curing of the product occurs in 24 hours, during this period the place must be well ventilated, to prevent the accumulation of vapors. In buildings, the windows should be open and in vehicles, the windows should be lowered. Note: the number of coats will depend on the weave of the fabric. More open weave fabrics should receive a greater number of coats, waiting 5 minutes between them. Compatibility test: apply the product in an area that is not so visible until it is moistened. Dry the area with a white or absorbent tissue. If the color changes to the white fabric or the area is stained, do not use the product. Efficiency test: after 24 hours of application, pour a little water and check if the repellency has occurred. Reapply if it does not reach the expected efficiency. ATTENTION: This product does not protect fabrics from urine, lipstick and paints. This product is not a permanent waterproofing product, it requires re-application. Do not use on carpet, carpet, leather, suede, suede and plastics. If in doubt, test the product in an unexposed area. To maintain the benefits of fabric protection, dust and dirt must be removed from the fabric using a vacuum cleaner once or twice a week. Remove spilled liquid on treated parts using an absorbent paper without ever compressing it, as this would cause the liquid to penetrate the fabric fibers.

### PERFORMANCE

2 (two) 400mL cans per vehicle (front and rear seats). During application, only the applicator must remain in place, using a mask with a filter for organic vapors. During application, avoid contact with acrylic materials, vinyls or pieces with varnish soluble in acetone. Some types of wooden carpets, floors, parquet floors or stones may also change with the product. It is recommended to protect floors in case of applications close to those places.

### LIMITATIONS

Before using this or any other chemical, make sure you have read and understood the information contained in the Safety Data Sheet (SDS). Observe the potential risks and follow all precautionary measures, handling instructions, considerations and provisions mentioned in the MSDS and on the packaging.

### STORAGE

The product must be kept in its original packaging and stored in a cool place at a temperature of 5 to 30°C, protected from direct sunlight and away from heat sources, with the packaging always facing upwards. Do not expose to the sun and temperatures above 50°C. Avoid keeping the product inside vehicles. Keep out of reach of children and pets. Validity (from the date of manufacture): 24 months.

### LIMITED WARRANTY INFORMATION

The information contained in this Technical Data Sheet is based on our knowledge and experience up to the present date. Due to our product being able to be used in a wide range of applications and under different working conditions, we recommend that the customer conducts their own tests to approve the product for safety and intended use. We cannot assume responsibility for the results obtained by others whose methods are beyond our control. Therefore, it is the sole responsibility of the user to determine the suitability of the product for the desired purpose and to adopt any precautions that may be advisable to protect property and individuals against any hazards that may be involved in its handling and application. Our warranty applies within the context of legal regulations and provisions, professional standards in force, and in accordance with the determinations established in our general sales conditions. The detailed information in this document is provided for indicative purposes only. The same applies to any information provided verbally, by telephone, or in writing to any potential or existing customer. For safety, handling, storage, and disposal information, please consult the respective Material Safety Data Sheet (MSDS).



**unipega.com**

info@unipega.com

f /unipegaoficial

@unipega\_oficial

Unipega

Unipega